

Distributed by  
STIHL Incorporated  
536 Viking Drive  
Virginia Beach, VA 23452  
(757) 486-9100

Four Star Chemical 24-

HOUR

3137 26th Street

EMERGENCY

MATERIAL SAFETY

Los Angeles Ca 90023

TELEPHONE

DATA SHEET

(323) 266-7111

(800)

255-3924

K & N AIR FILTERS, INC.

#99-0516

AIR FILTER OIL, 12.25 OZ

PRODUCT ID NO.: 32603

PAGE: 1

\*\*\*\*\*  
\*\*\*\*\*

EFFECTIVE DATE: 08/27/07

PRODUCT ID NO.: 32603

DATE PREPARED: 08/27/07

=====  
=====

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200  
(The Hazard Communication Standard)

=====  
SECTION I - PRODUCT IDENTIFICATION

PRODUCT DESCRIPTION: K & N AIR FILTERS, INC.

AIR FILTER OIL, 12.25 OZ

D.O.T. PROPER SHIPPING NAME: ORM-D

CONSUMER COMMODITY

NFPA CODES: HEALTH - 1 FLAMMABILITY - 2 CORROSIVE - 0 REACTIVITY - 0

=====  
SECTION II - COMPONENTS

CUSTOMER SUPPLIED PRODUCT

PEL: NOT AVAILABLE

CAS #: NOT AVAILABLE

TLV: NOT AVAILABLE

HYDROCARBON PROPELLANT

PEL: 800 PPM

CAS #: 68476-86-8

TLV: 800 PPM



SEC05.22

ROUTES OF EXPOSURE:

INHALATION: Excessive inhalation may produce symptoms of central nervous system depression, ranging from light-headedness, nausea and vomiting, to unconsciousness and death.

SKIN: Mildly irritating to skin. Skin contact may produce a burning sensation--prolonged or repeated contact may cause skin to become redened, rough, and dry due to the removal of natural oils and may result in dermatitis.

May be absorbed through the skin, although not expected to produce toxicity through this route.

EYE CONTACT: An irritant of the eyes, causing pain, lacrimation and general inflammation.

INGESTION: May cause irritation of the gastrointestinal tract with vomiting. If vomiting results in aspiration, chemical pneumonia may follow. Absorption through the gastrointestinal tract may produce symptoms of central nervous system depression ranging

from

light headedness to unconsciousness.

EFFECTS OF OVEREXPOSURE:

ACCUTE: Excessive inhalation or ingestion may produce symptoms of central nervous system depression ranging from light headedness, to unconsciousness and death. Overexposure may result in liver and kidney damage. Exposure of the eyes and skin may produce irritation. Animals exposed to high levels have shown cardiac sensitization.

fatigue,  
CHRONIC: Can cause headache, mental confusion, depression, loss of sense of balance, and visual disturbances. Prolonged or repeated skin contact may cause dermatitis.

HYGIENE: Avoid contact with skin and avoid breathing vapors. Do not eat, drink or smoke in work area. Wash hands prior to eating, drinking or using restroom.

FIRST AID:

EYES: Irrigate with flowing water immediately and continuously for 15 minutes. Consult medical personnel.

SKIN: Wash off in flowing water or shower.

HOUR  
EMERGENCY

Four Star Chemical  
3137 26th Street

24-

MATERIAL SAFETY  
TELEPHONE  
DATA SHEET  
255-3924

Los Angeles Ca 90023  
(323) 266-7111

(800)

K & N AIR FILTERS, INC.  
AIR FILTER OIL, 12.25 OZ

PRODUCT ID NO.: 32603

PAGE: 3

\*\*\*\*\*  
\*\*\*\*\*

===== SECTION V - HEALTH HAZARD DATA(CONTINUED) =====

INGESTION: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

NOTE TO PHYSICIAN: Because rapid absorption may occur through lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighted against toxicity when considering emptying the stomach. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs unless absolutely necessary.

===== SECTION VI - REACTIVITY DATA =====

06.20

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

===== SECTION VII - SPILL OR LEAK PROCEDURES =====

SEC07.45

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbant materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal

procedures. Empty de-pressurized containers can not be reused.  
Cans

which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

=====  
SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED  
SEC08.22

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded.

OTHER CLOTHING EQUIPMENT: Standard work clothing.

HOUR	Four Star Chemical	24-
	3137 26th Street	
EMERGENCY		
MATERIAL SAFETY	Los Angeles Ca 90023	
TELEPHONE		
DATA SHEET	(323) 266-7111	(800)
255-3924		

K & N AIR FILTERS, INC.  
AIR FILTER OIL, 12.25 OZ

PRODUCT ID NO.: 32603 PAGE: 4  
\*\*\*\*\*

=====  
SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED (CONTINUED) ====  
Standard work shoes; discard if shoes cannot be decontaminated.  
Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

MONITORING EXPOSURE:

BIOLOGICAL: No applicable procedures can be recommended.  
PERSONAL/AREA: Use NIOSH ANALYTICAL METHOD NUMBER 1003 for halogenated hydrocarbons.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

=====  
SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS  
SEC09.45

HANDLING STORAGE AND DECONTAMINATION PROCEDURES: When utilizing pressurized

containers follow standard safety practices for handling aerosols.

GENERAL COMMENTS: Do not store at temperatures above 120 degree F. Odor is not an adequate warning of potentially hazardous concentrations in air. Releases of these gases may cause a flammable atmosphere with explosion potential.

PRECAUTIONARY STATEMENTS: Please read and follow the directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

===== ADDITIONAL COMMENTS =====

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.